



Overview of Evapotranspiration

Amita Mehta, Ana Prados, Erika Podest

December 2017

Learning Objectives

- Understand methods of estimating evapotranspiration (ET) using remote sensing
 - Identify NASA satellites and sensors used for ET estimation
 - Access ET data

Presentation Outline

- Importance and Challenges of ET Estimation
- Methods of Estimating ET Based on Remote Sensing
- Overview of ET Data Products
- Applications of ET data
- METRIC: Mapping Evapotranspiration at high-Resolution with Internalized Calibration



Importance and Challenges of ET Estimation

What is Evapotranspiration (ET)?

- The sum of evaporation from the land surface, plus transpiration from plants
- ET transfers water from the surface to the atmosphere in vapor form
- Energy is required for ET to take place (for changing liquid water into vapor)



Importance of ET

- Critical component of the water and energy balance of climate-soilvegetation interactions
- Useful for:
 - determining agricultural water consumption
 - assessing drought conditions
 - developing water budgets
 - monitoring aquifer depletion
 - monitoring crops and carbon budgets

Challenges in Measuring ET

- ET depends on many variables:
 - solar radiation at the surface
 - land and air temperatures
 - humidity
 - surface winds
 - soil conditions
 - vegetation cover and types
- Highly variable in space and time




Image Credit: NASA Earth Observatory, Robert Simmon, based on data from the Idaho Department of Water Resources



ET Ground Measurements

- Limitation
 - Point measurements and cannot capture spatial variability

Eddy Covariance System





Lysimeters

Image Credit: (left) AmeriFlux, Dept of Energy; (right) USGS




Benefits of Estimating ET from Remote Sensing Data

 Provide relatively frequent and spatially continuous measurement of biophysical variables used in estimating ET at different spatial scales including:

- radiation
- land surface temperatures
- vegetation coverage and density
- precipitation
- soil moisture
- weather and climate variables

Global ET Based on MODIS, Averaged over 2000-2006



Source: University of Montana, Numerical Terradynamic Simulation Group






Methods of Estimating ET Based on Remote Sensing

Remote Sensors and Observations for ET

| Satellite | Sensor | Parameter | |
|----------------|-----------------|---|--|
| Terra and Aqua | MODIS | Normalized Difference Vegetation Index (NDVI) Leaf Area Index (LAI) Albedo (fraction of surface solar radiation reflected back) | |
| Landsat | OLI, ETM+, TIRS | Spectral ReflectanceThermal Emission | |

Importance of Landsat for ET

- Allows field-level ET (30 m resolution) much higher resolution than MODISbased ET (1 km)
- Has a thermal band that is important for some ET approaches





Estimation of ET – not easy!

- ET can be derived primarily from:
 - Surface Water Balance
 - ET = Precipitation + Irrigation Runoff Ground Water + Vertical Water
 Transport ± Subsurface Flow ± Soil Water Content
 - Surface Energy Balance
 - ET (Latent Heat Flux) = Net Surface Radiation Ground Heat Flux Sensible Heating Flux
 - Meteorological and Vegetation/Crop Data (Penman-Monteith Equation)



ET Estimation by Land Surface Models

Integrate satellite and ground observations within sophisticated numerical models based on water and energy balance methods

Remote Sensing Inputs

- Surface Solar Radiation
 - from atmospheric models with satellite data assimilation
- Precipitation (TRMM and Multi-Satellites)
- Vegetation Classification & Leaf Area Index (MODIS & AVHRR)
- Topography (Landsat)


Integrated Outputs

- Soil Moisture
- Evapotranspiration
 - Surface/Sub-Surface Runoff
 - Snow/Water Equivalent

Global Land Data Assimilation System (GLDAS): http://ldas.asfc.nasa.aov


ET Estimation by Surface Energy Balance

- Used by multiple groups to develop ET products
- Uses MODIS & Landsat
 - land surface temperatures
 - land cover
- Calculated by a "residual" of the energy balance – driven by thermal energy



ET Estimation from Vegetation and Crop Information

4. Reference (ET_o), crop evapotranspiration under standard (ET_c) and non-standard conditions (ET_{c adi})



- ET_o: reference ET for well-watered grass reference (Penman-Moneith Equation)
- ET_c: crop ET for standard crop conditions:
 - disease free, well fertilized, grown in large fields, optimum soil water conditions, achieving full production under given climatic conditions
- ET_{c adj}: adjusted for non-standard crop conditions
- K_c: crop coefficient

Image Credit: http://www.fao.org/docrep/X0490E/x0490e04.htm#determining%20evapotranspiration



Penman-Monteith Equation for ET_o

$$\lambda ET = [\Delta(R_n - G) + \rho_a C_p(e_s - e_a)/r_a]/[\Delta + Y(1 + r_s/r_a)]$$


- Δ: slipe of saturation vapor pressure
- R_n: net surface radiation
- G: ground heat flux
- (e_s-e_a): vapor pressure deficit
- r_a & r_s: aerodynamic & surface resistance
- γ: psychrometric constant
- λ: latent heat constant
- c_p: specific heat constant
- ρ_a: Air density


- Requires climate and crop information
- r_a & r_s depend on Vegetation Height, Leaf Area Index (LAI)
- R_n depends on the fractional solar radiation reflected back from the surface (albedo)
- LAI and albedo are both available from MODIS

Reference: http://www.fao.org/docrep/X0490E/x0490e06.htm#penman%20monteith%20equation

Crop Coefficient (K_c) and Normalized Vegetation Index (NDVI)

- K_c is related to light interception (ground cover)
- There is a direct relationship between K_c and NDVI
 - available from MODIS







^{*} Image Credits: Tom Trout, USDA



ET Data Products Based on Remote Sensing

ET Data Products Based on Remote Sensing Observations Global Products

- METRIC: Mapping and EvapoTranspiration at high-Resolution with Internalized Calibration
 - https://c3.nasa.gov/water/static/media/other/Day1_S1-3_Allen.pdf
 - https://c3.nasa.gov/water/static/media/other/Day1_S2-5_Kilic.pdf
 - https://c3.nasa.gov/water/static/media/other/Day1_S3-3_Allen.pdf
- ALEXI: Atmosphere-Land Exchange Inverse Model
 - https://c3.nasa.gov/water/static/media/other/Day1_S1-4_Anderson.pdf
 - http://www.ospo.noaa.gov/Products/land/getd/index.html
- GLDAS: Global Land Data Assimilation System
 - http://ldas.gsfc.nasa.gov/gldas/

ET Data Products Based on Remote Sensing Observations Regional Products (can be adapted for other regions)

- SIMS: Satellite Irrigation Management Support (California)
 - https://c3.nasa.gov/water/static/media/other/Day1_S2-2_Melton.pdf
- NLDAS: North American Land Data Assimilation System (North America)
 - http://ldas.gsfc.nasa.gov/nldas
- SSEBop: Operational Simplified Surface Energy Balance (US & Africa)
 - http://www2.usgs.gov/climate_landuse/lcs/projects/wsmartet.asp
- ETWatch: Multi-Satellite Based Energy Balance Model (China)
 - https://c3.nasa.gov/water/static/media/other/Day2_S1-4_Wu_2.pdf

Summary: Publically Available Global ET Products

| ET Source | Method | Remote Sensing Observations |
|-----------|---|--|
| GLDAS | Land Surface ModelWater and Energy Balance | TRMM & Multi-Satellite Precipitation MODIS and AVHRR Land Cover Landsat Topography |
| METRIC | Energy Balance | • Landsat |
| ALEXI | • Energy Balance | MODISLandsatGOES |

| ET Source | Spatial/Temporal Resolution | Data Source | Availability |
|-----------|---|--|---------------------------------------|
| METRIC | 30 m (Global)2011 – March 2016 | Google Earth Engine Evapotranspiration Flux (EEFlux) | http://eeflux- level1.appspot.com/ |



Applications of ET

ET for Irrigation Management

http://ec2-54-196-147-232.compute-1.amazonaws.com/dgw/sims/

- Beta web interface complete
- Web tool publicly accessible
- Being tested by multiple growers
- Integrated with UCCE CropManage irrigation management tool
- Prototype calculator for on-farm water use efficient metrics completed


TOPS Satellite Irrigation Management Support Crop Coefficient Kcb Fractional Cover

Reference: https://c3.nasa.gov/water/static/media/other/Dav1 S2-3 Mendez.pdf

ET for Irrigation Management

http://ec2-54-196-147-232.compute-1.amazonaws.com/dgw/sims/


 Landsat-based ET helps wine producers and grape growers in California plan timing and irrigation




Reference: https://c3.nasa.gov/water/static/media/other/Day1 S2-3 Mendez.pdf




ET for Drought Monitoring Over North America





ET for Water Allocation

- METRIC ET used for deciding water deficit
- Example
 - based on the ET and NDVI analysis, Idaho Department of Water Resources verified that certain fields claimed to be water deficient were not




Purple polygons are fields that claimed to be water short in 2006

Reference: https://c3.nasa.gov/water/static/media/other/Day1 S1-3 Allen.pdf

ET for Water Allocation

- The impact of water management decisions were more visible than climate drivers on crop water use (evapotranspiration) changes over time
- The SSEBop ET modeling approach was stable in processing 3,396
 Landsat images and generating reliable estimates for trend analysis
- Quantified the association between crop fallowing programs and water savings




Median annual ET estimates for the Palo Verde Irrigation District (PVID) obtained from the SSEBop model over 1984-2014. Also shown are selected time-series imagery of ET for every 5 years since 1985. Image credit: Senay et al.

Reference: Senay, G., et al. Landsat based historical (1984-2014) crop water use estimates and trends in the Southwestern United States. AGU 2016. https://landsat.gsfc.nasa.gov/watchina-water-use-in-the-southwest/

ET Used in Planning for Aquifer Management

METRIC ET, together with precipitation, helped estimate Ogalalla Aquifer Recharging


Evapotranspiration minus precipitation for April 1- Oct 31, 1997, Path 33, Row 31



Reference: https://c3.nasa.gov/water/static/media/other/Day1 \$1-3 Allen.pdf

ET Used in Agriculture Water Use in China

- Based on ET from ETWATCH and rainfall data excessive use of water for agriculture was noted 2008-2013
- Very useful for planning water resource allocation






Reference: https://c3.nasa.gov/water/static/media/other/Day1 \$1-3 Allen.pdf

ET Used to Track Agricultural Water Consumption

- Estimated agricultural water consumption (AWC) based on station data (1984-2008) and MODIS ET data
- Found AWC increased significantly in the past 25 years, with the exception of a few counties
- The integration of meteorological and satellite data allows for the estimation of actual ET beyond the record available from satellite data



Distribution of annual mean ET_0 (a), actual ET (b), and changes in averaged ET for the period of 1984–1993 to 1999–2008 (c).

Reference: Yuan, Z., & Shen, Y. (2013). Estimation of Agricultural Water Consumption from Meteorological and Yield Data: A Case Study of Hebei, North China. PLoS ONE, 8(3). doi:10.1371/journal.pone.0058685






METRIC: Mapping EvapoTranspiration at high-Resolution with Internalized Calibration

METRIC: Based on Energy Balance


- Energy Balance (EB)
 - Remember: ET is the water that changes from liquid to water vapor
 - Liquid to vapor conversion requires energy
 - We "look" for the energy used to produce the evaporation
 - EB components can be derived from the temperature of the surface


ET is Calculated as a Residual of the Energy Balance



ET Is Influenced More by Surface Temperature Than Vegetation

Middle Rio Grande, New Mexico





General EB Components in METRIC

METRIC uses Landsat band reflectances and weather information to get the EB components

- Net Radiation (R_n)
 - Reflected shortwave from satellite
 - Incoming shortwave from theory
 - Emitted longwave from satellite
 - Incoming longwave from emitted and atmospheric transmissivity
- Soil Heat Flux (G)
 - Function of H for nearly bare soil and function of Rn for vegetation
- $\lambda E = R_n G H$

Reference: Allen, R. G., et al. (2007). Satellite-Based Energy Balance for Mapping Evapotranspiration with Internalized Calibration (METRIC)—Applications. Journal of Irrigation and Drainage Engineering, 133(4), 395-406. doi:10.1061/(asce)0733-9437(2007)133:4(395)

General EB Components in METRIC


METRIC uses Landsat band reflectances and weather information to get the EB components

- Sensible Heat Flux (H)
- Near surface vertical air temperature gradient (dT) keyed from surface temperature (Ts) – calibrated to each image date (dT = a + b Ts)
- Aerodynamic resistance from
 - Wind speed at blending height (from gridded or local weather)
 - Aerodynamic roughness from vegetation indices and land use type
 - Buoyancy effects from iterative solutions




Comparison of Seasonal ET by METRIC with Lysimeter


Sugar Beets April – Sept 1989, Kimberly, Idaho




EEFlux: METRIC Data Access from Google Earth Engine




EEFlux: Google Earth Engine Based METRIC ET



EEFlux: Google Earth Engine Based METRIC ET



EEFlux: Google Earth Engine Based METRIC ET



Summary

- Evapotranspiration is not measured, but calculated by water and/or energy balance methods
- Requires complex algorithm and a variety of climate and land surface data
- Multiple algorithms for estimating ET are available validation and intercomparison for regional use are recommended
- Remote sensing data from Landsat and MODIS (land surface temperature, land cover, vegetation index, leaf area index, albedo) are very useful in estimating ET
- For more details see ARSET Webinar on ET:
 - https://arset.gsfc.nasa.gov/water/webinars/apps-et-smap



Next Hands-on Exercise: ET Data Download for Sau Francisco Watershed